CATION PUBLISHED UNDER THE PATENT COPERATION TREATY (PCT) (12) INTERNATIONAL A

(19) World Intellectual Property Organization

International Bureau

Rec'd PCT/PTO 20 JUL 2005

WO 2004/066452 A1

PCT

(43) International Publication Date 5 August 2004 (05.08.2004)

(51) International Patent Classification7:

H01R 13/639

(21) International Application Number:

PCT/AU2004/000064

(22) International Filing Date: 20 January 2004 (20.01.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2003900291 2003902257

20 January 2003 (20.01.2003) ΑU 9 May 2003 (09.05.2003) AU

- (71) Applicant (for all designated States except US): HEAD ELECTRICAL INTERNATIONAL LTD [AU/AU]; 1 Cooper Street, Dudley, New South Wales 2290 (AU).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): WELLS, Mark [AU/AU]; 1 Cooper Street, Dudley, New South Wales 2290 (AU).


- (74) Agent: GRIFFITH HACK; GPO Box 4164, Sydney, New South Wales 2001 (AU).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

[Continued on next page]

(54) Title: ELECTRICAL CONNECTION DEVICE



(57) Abstract: The present invention provides an electrical connection device (20), which comprises a pin (22) and a socket (24). The pin and the socket have engagement surfaces and one of the pin and the socket has a further surface that forms a wedging surface (25) for the device. The pin (22) and the socket (24) are moveable relative to each other to form an electrical contact. The device further comprises a wedge portion (25), which is arranged to impart a force on the wedging surface by contacting the wedging surface on movement to the engaged position. The pin and the socket are arranged so that the engagement surfaces move into opposing relationship on movement to the engaged position and the force imparted on the wedging surface biases one of the opposing engagement surfaces against the other engagement surface.